

**Product code**

71 10 00G

**Product description**

Universal hood chemically resistant

**Standards**EN 12941 TH3,  
EN 14594 3A**Protection of respiratory tract**

when used with:

- CleanAIR® PAPR systems provides level of protection up to TH3 according to EN 12941
- CleanAIR® compressed air line systems provides level of protection 3A according to EN 14594

**Weight**

250 g

**Product dimensions**

150 mm / 450 mm / 300 mm

**Visor dimensions**

270 x 150 mm

**Colour**

grey

**Materials**

Hood - polyester with PVC coating  
Hose connector / Exhalation valve - ABS  
Headband - Polyamid PA6  
Visor - Plasticized cellulose propionate  
Canvas - Tychem® F

**Recommended hose type**

70 00 60 - Light flexi hose  
Internal thread CA40x1/7" - external thread CA40x1/7"  
Lenght: seft adjusting; 600 mm - 1 100 mm / Weight: 150 g

**Storage conditions**

-10 °C to + 55 °C, humidity 20 - 80 % RH  
avoid long exposure of UV radiation

**Operating conditions**

+10 °C to + 40 °C, humidity 20 - 80 % RH

## Spare parts and accessories

| product code | product description   |
|--------------|---|
| 70 00 60     | Light flexi hose CA40x1/7" - CA40x1/7" - straight connector   |
| 70 00 60B    | Light flexi hose CA40x1/7" - bayonet - straight connector     |
| 70 00 86CA   | Rubber hose CA40x1/7" - CA40x1/7" - straight connector        |
| 70 00 86B    | Rubber hose CA40x1/7" - bayonet - straight connector          |
| 70 01 20     | Protection plate (suitable for CA-1, CA-2 and CA-10 - 10 pcs) |
| 16 70 01     | Sweatband CleanAIR®   |
| 71 01 10     | Winter cap + sweatband  |
| 70 00 62C    | Hose cover chemical resistant                                 |

## Compatible respiratory units (According to EN 12941)

| product code | product description            | level of protection |
|--------------|--------------------------------|---------------------|
| 30 00 00PA   | CleanAIR® AerGO®               | TH3                 |
| 51 00 00FCA  | CleanAIR® Chemical 2F          | TH3                 |
| 52 00 00FCA  | CleanAIR® Chemical 3F          | TH3                 |
| 80 00 00XPA  | CleanAIR® Basic 2000 DF        | TH1                 |
| 82 00 00PA   | CleanAIR® Basic 2000 FC        | TH3                 |
| 67 00 00     | CleanAIR® Pressure Flow Master | 3A                  |

(According to EN 14594)

## Areas of application

Universal hood CA-10 consist of chemically resistant visor and an integrated air distribution system. The adjustable headband ensures perfect fitting (the head circumference and height are adjustable in three levels). The size of the hood can be adjusted at two points - on the neck and scruff. The wide panoramatic visor enables good orientation and has a special anti-fog coating. This hood is made out of the chemically resistant canvas with taped seams, and is resistant against wide range of acids and solvents.

Universal hood CA-10 provides sufficient protection of the breathing paths and protect the foreface against splashing of dangerous fluids.

Universal hood CA-10 finds application in many sectors like chemical industry, painting operations, laboratories, pharmaceutical industry, etc.

## Limitations



- Please, read carefully relevant instruction for use and follow your national safety regulations for PPE.